

Architectural drawing showing a plan view of a ramp and staircase. The ramp is labeled "NAVRHOVANÁ NAŠŤAPNÁ VRSTVA RAMPY – GRESOVÁ PROTIŠMYKOVÁ DLAŽBA HR. 20mm". The drawing includes dimensions for the ramp (1500, 1280, 150, 40, 120, 1400, 1090, 1200, 2150, 2200, 1060, 1060, 1060, 510, 20, 40, 120) and a section view (POHLAD B) showing a 1:8 slope. A callout indicates the ramp surface is made of 20mm thick anti-slip tiles. A staircase is shown to the right with a 1970mm width and 740mm/1970mm riser/run dimensions. A section view (POHLAD C) is also shown at the top left.

[illegible]

Technical drawing of a staircase showing side and front elevations with dimensions.

Side Elevation (Left):

- Total height: 900
- Top section height: 200
- Section height: 700
- Section height: 600
- Section height: 300
- Section height: 260
- Section height: 40
- Section height: 40
- Section height: 160
- Section height: 40

Front Elevation (Right):

- Total width: 1200
- Top section width: 150
- Section width: 1090
- Section width: 270
- Section width: 330
- Section width: 900
- Section width: 360
- Section width: 40
- Section width: 40
- Section width: 160
- Section width: 40
- Section width: 300
- Section width: 600
- Section width: 900

Other Dimensions:

- Staircase slope: 1:8
- Staircase width: 300
- Staircase height: 600
- Staircase width: 40
- Staircase height: 40
- Staircase width: 160
- Staircase height: 40
- Staircase width: 360
- Staircase height: 40
- Staircase width: 260
- Staircase height: 40

The technical drawing illustrates a rectangular frame assembly with the following dimensions and components:

- Overall Dimensions:**
 - Total width: 1500
 - Total height: 900
- Internal Dimensions and Spacing:**
 - Top horizontal distance from left edge to start of main section: 100
 - Main top horizontal distance: 1410
 - Distance between vertical bars: $\bar{a}_{\max} = 80 \text{ mm}$
 - Right side margin: 160
 - Bottom right corner offset: 20
- Vertical Section Dimensions (Left Side):**
 - Top section height: 200
 - Middle section height: 700
 - Bottom section height: 660
 - Small bottom offsets: 60 and 40
- Vertical Section Dimensions (Right Side):**
 - Top section height: 40
 - Section below top: 360
 - Section below middle: 600
 - Section below bottom: 700
 - Bottom section height: 900
 - Small bottom offsets: 80, 20, 40, 60
- Component Labels:**
 - ① ⑥: Bottom corners
 - ②: Right side vertical elements
 - ③: Vertical bars
 - ④: Horizontal bars
 - ⑤: Top right corner element

- ① STLPIK – OCELOVÝ JÁKLOVÝ PROFIL 40x40x2 mm
KOTVENIE Z HORA POMOCOU CHEMICKEJ KOTVY 4xø 10 mm DL. 150mm – KOTVENIE DO ŽELEZOBETÓNOVEJ KONŠTRUKCIE
- ② KONŠTRUKCIA ZÁBRADLIA – OCELOVÁ RÚRKA ø 20 mm
- ③ VÝPLŇ ZÁBRADLIA – OCELOVÁ RÚRKA ø 10 mm
- ④ MADLO ZÁBRADLIA – OCELOVÁ RÚRKA ø 50 mm
- ⑤ OCELOVÝ KOTVIACI ÚCHYT MADLA – TRUBKA ø15 mm
- ⑥ OCELOVÁ KOTVIACA PRÍRUBA PÄTKY – ROZMER 100x100x8 mm, 24–KRÁT CHEMICKÁ KOTVA DO BETÓNU

- BEZPEČNOSTNÉ ZÁBRADLIE BUDE VYHOTOVENÉ Z NEREZOVEJ OCELE;
- PRED ZADANÍM DO VÝROBY PREMERAŤ PRIAMO NA STAVBE. SPÔSOB UKOTVENIA ZOSÚLADIŤ PRIAMO NA STAVBE S DODÁVATEĽOM;
- PRI VÝROBE ZOHLADŇOVAŤ HRúbKU ZATEPLENIA OBJEKTU;
- PRI JEDNOTLIVÝCH PROFILOCH POUŽIŤ OBLÉ HRANY;
- V SÚLADE S STN 74 3305 OCHRANNÉ ZÁBRADLIA;
- OCEĽ – SYNTETICKÝ NÁTER (1x ZÁKLADNÝ + 2x VRCHNÝ NÁTER);

AUTOR NÁVRHU	Bc. DENISA ŠKULTÉTYOVÁ	
ZODP. PROJEKTANT	ING. MÁRIO KLOPAN	
VYPRACOVAL	Bc. DENISA ŠKULTÉTYOVÁ	
STAVEBNÍK	MESTO STARÁ TURÁ GEN. M. R. ŠTEFÁNKA 375/63, 916 01 STARÁ TURÁ	

Nám. J. C. Hronského 12, 971 01 Prievidza
e-mail: mario.klopan@ergaprojekt.sk
tel.: 0905 763 596

STAVBA	DEBARIERIZÁCIA DOMU KULTÚRY JAVORINA	ČÍSLO ZÁKAZKY	25-056
--------	---	---------------	--------

ČASŤ	ASR. ARCHITEKTONICKO STAVEBNÉ RIEŠENIE	FORMÁT	2xA4
------	--	--------	------

OBSAH VÝKRESU	PÔDORYS RAMPY A ZÁBRADLIE - - ĽAVÁ STRANA, NAVRHOVANÝ STAV	ČÍSLO VÝKRESU	013
---------------	---	---------------	-----